

SERVICE SPECIFICATIONS

SERVICE DATA

BR15B-01

Pedal height from floor panel		151.5 mm (5.985 in.)
Stop light switch and pedal clearance		0.5–2.4 mm (0.020–0.094 in.)
Brake pedal freeplay		1–6 mm (0.04–0.24 in.)
Brake pedal reserve distance at 490 N (50 kgf, 110.2 lbf)		More than 58 mm (2.28 in.)
Front brake pad thickness	STD	10.0 mm (0.394 in.)
	Minimum	1.0 mm (0.039 in.)
Front brake disc thickness (14 in. Type)	STD	25.0 mm (0.984 in.)
	Minimum	23.0 mm (0.906 in.)
Front brake disc thickness (15 in. Type)	STD	28.0 mm (1.102 in.)
	Minimum	26.0 mm (1.023 in.)
Front brake disc runout	Maximum	0.09 mm (0.0035 in.)

BR15B-01

TORQUE SPECIFICATION

Part tightened	N·m	kgf·cm	ft·lbf
Pedal push rod lock nut	25	260	19
Front brake caliper installation bolt	(14 in. Type)	39	29
	(15 in. Type)	34	25
Front disc brake caliper x Flexible hose	30	310	22
Front brake disc x Axle hub	(14 in. Type)	68	51
	(15 in. Type)	72	53
Front brake torque plate x Steering knuckle	147	1,500	108
Bleeder plug	11	110	8
LSP & BV x LSP & BV bracket	13	130	9

BR