

2017 SUSPENSION**CHEVROLET WHEEL ALIGNMENT SPECIFICATIONS - BOLT****WHEEL ALIGNMENT SPECIFICATIONS****BOLT EV 205/55 R16****BOLT EV 205/55 R16**

Measurement	Minimum	Preferred	Maximum
Left Front Caster ($\hat{A}^\circ$)	4.75	5.5	6.25
Right Front Caster ($\hat{A}^\circ$)	4.75	5.5	6.25
Left Front Camber ($\hat{A}^\circ$)	-1.3	-0.55	0.2
Right Front Camber ($\hat{A}^\circ$)	-1.3	-0.55	0.2
Front Toe ($\hat{A}^\circ$)	-0.18	0.02	0.22
Left SAI ($\hat{A}^\circ$)	0	0	0
Right SAI ($\hat{A}^\circ$)	0	0	0
Left Rear Camber ($\hat{A}^\circ$)	-1.9	-1.4	-0.9
Right Rear Camber ($\hat{A}^\circ$)	-1.9	-1.4	-0.9
Rear Toe ($\hat{A}^\circ$)	-0.15	0.2	0.55
Thrust Angle	0.3	0	0
Left Toe Out, Inward ($\hat{A}^\circ$)	0	0	0
Right Toe Out, Inward ($\hat{A}^\circ$)	0	0	0
Left Toe Out, Outward ($\hat{A}^\circ$)	0	0	0
Right Toe Out, Outward ($\hat{A}^\circ$)	0	0	0
Left Max Turn, Inward ($\hat{A}^\circ$)	0	0	0
Right Max Turn, Inward ($\hat{A}^\circ$)	0	0	0
Left Max Turn, Outward ($\hat{A}^\circ$)	0	0	0
Right Max Turn, Outward ($\hat{A}^\circ$)	0	-	-

BOLT EV 215/50 R17**BOLT EV 215/50 R17**

Measurement	Minimum	Preferred	Maximum
Left Front Caster ($\hat{A}^\circ$)	4.75	5.5	6.25
Right Front Caster ($\hat{A}^\circ$)	4.75	5.5	6.25
Left Front Camber ($\hat{A}^\circ$)	-1.3	-0.55	0.2
Right Front Camber ($\hat{A}^\circ$)	-1.3	-0.55	0.2
Front Toe ($\hat{A}^\circ$)	-0.18	0.02	0.22
Left SAI ($\hat{A}^\circ$)	0	0	0
Right SAI ($\hat{A}^\circ$)	0	0	0
Left Rear Camber ($\hat{A}^\circ$)	-1.9	-1.4	-0.9
Right Rear Camber ($\hat{A}^\circ$)	-1.9	-1.4	-0.9
Rear Toe ($\hat{A}^\circ$)	-0.15	0.2	0.55
Thrust Angle	0.3	0	0
Left Toe Out, Inward ($\hat{A}^\circ$)	0	0	0
Right Toe Out, Inward ($\hat{A}^\circ$)	0	0	0
Left Toe Out, Outward ($\hat{A}^\circ$)	0	0	0
Right Toe Out, Outward ($\hat{A}^\circ$)	0	0	0
Left Max Turn, Inward ($\hat{A}^\circ$)	0	0	0
Right Max Turn, Inward ($\hat{A}^\circ$)	0	0	0
Left Max Turn, Outward ($\hat{A}^\circ$)	0	0	0

Measurement	Minimum	Preferred	Maximum
Right Max Turn, Outward (Â°)	0	-	-
