

0 GENERAL

VEHICLE IDENTIFICATION 0-2

MAJOR SPECIFICATIONS 0-4

VEHICLE IDENTIFICATION

MODELS

VEHICLES FOR GENERAL EXPORT

(Except for CENTRAL AND SOUTH AMERICA COUNTRIES, BRAZIL, HONG KONG, SOUTH AFRICA)

Model code		Engine model	Transmission model	Fuel supply system
H65	WMNUEL	4G18-SOHC (1,584 ml)	V5M21 <5M/T>	MPI
	WMNUER			
	WMRUEL		V4AW4 <4A/T>	
	WMRUER			
H76	WLNUEL	4G93-SOHC (1,834 ml)	V5M21 <5M/T>	
	WLNUER			
	WLRUEL		V4AW4 <4A/T>	
	WLRUER			

(VEHICLES FOR CENTRAL AND SOUTH AMERICA COUNTRIES)

Model code		Engine model	Transmission model	Fuel supply system
H65	WMNUEL1NQ	4G18-SOHC (1,584 ml)	V5M21 <5M/T>	MPI
	WMRUEL1NQ		V4AW4 <4A/T>	
H76	WLNUEL1NQ	4G93-SOHC (1,834 ml)	V5M21 <5M/T>	
	WLRUEL1NQ		V4AW4 <4A/T>	

(VEHICLES FOR BRAZIL)

Model code		Engine model	Transmission model	Fuel supply system
H76	WLNUEL1FB	4G93-SOHC (1,834 ml)	V5M21 <5M/T>	MPI
	WLRUEL1FB		V4AW4 <4A/T>	

(VEHICLES FOR HONG KONG)

Model code		Engine model	Transmission model	Fuel supply system
H66	WMNUCR1D	4G93-DOHC (1,834 ml)	V5M21 <5M/T>	GDI
	WMRUCR1D		V4AW4 <4A/T>	
H76	WLNUCR1D		V5M21 <5M/T>	
	WLRUCR1D		V4AW4 <4A/T>	

(VEHICLES FOR SOUTH AFRICA)

Model code		Engine model	Transmission model	Fuel supply system
H65	WMNUER1S	4G18-SOHC (1,584 ml)	V5M21 <5M/T>	MPI
H76	WLNUE1S	4G93-SOHC (1,834 ml)	V5M21 <5M/T>	
	WLRUE1S		V4AW4 <4A/T>	

VEHICLES FOR GCC

Model code		Engine model	Transmission model	Fuel supply system
H65	WMNUELW	4G18-SOHC (1,584 ml)	V5M21 <5M/T>	MPI
	WMRUELW		V4AW4 <4A/T>	
H76	WLNUELW	4G93-SOHC (1,834 ml)	V5M21 <5M/T>	
	WLRUELW		V4AW4 <4A/T>	

VEHICLES FOR AUSTRALIA AND NEW ZEALAND

Model code		Engine model	Transmission model	Fuel supply system
H65	WMNUER8	4G18-SOHC (1,584 ml)	V5M21 <5M/T>	MPI
H76	WLNUE8	4G93-SOHC (1,834 ml)	V5M21 <5M/T>	
	WLRUE8		V4AW4 <4A/T>	

MAJOR SPECIFICATIONS

VEHICLES FOR GENERAL EXPORT

(Except for CENTRAL AND SOUTH AMERICA COUNTRIES, BRAZIL, HONG KONG, SOUTH AFRICA)

Items	H65	H76
	WMNUEL, WMNUER WMRUEL, WMRUER	WLNUEL, WLNUER WLRUEL, WLRUER
Dimensions mm		
Overall length	3,730, 3,760* ¹	4,030, 4,060* ¹
Overall width	1,680	1,680, 1,695* ²
Overall height (unladen)	1,690, 1,730* ³ , 1,735* ⁴	1,700, 1,740* ³ , 1,725* ⁴
Wheelbase	2,280	2,450
Track-front	1,435	1,435
Track-rear	1,445	1,445
Body overhang		
Front	660	660
Rear	505	635
Ground clearance (unladen)	195	195
Wheel alignment		
Front wheel alignment		
Toe-in (at the centre of tyre tread) mm	3 ± 2	
Toe angle (per wheel)	0°07' ± 05'	
Camber	0°30' ± 30'	
Caster	3°00' ± 30'	
Kingpin inclination angle	11°04'	
Rear wheel alignment		
Toe-in (at the centre of tyre tread) mm	0	
Camber	0°	
Wheels and tyres		
Tyre size	205/65R15 94H	
Wheel size	16 × 6JJ	
Offset mm	46	

NOTE

(1) *¹: indicates vehicles with bumper extension.

(3) *³: indicates vehicles with roof rail.

(2) *²: indicates vehicles with side moulding.

(4) *⁴: indicates vehicles with roof spoiler.

(VEHICLES FOR CENTRAL AND SOUTH AMERICA COUNTRIES)

Items	H65	H76
	WMNUEL1NQ WMRUEL1NQ	WLNUEL1NQ WLRUEL1NQ
Dimensions mm		
Overall length	3,730, 3,760* ¹	4,030, 4,060* ¹
Overall width	1,680	1,680, 1,695* ²
Overall height (unladen)	1,690, 1,730* ³ , 1,735* ⁴	1,700, 1,740* ³ , 1,725* ⁴
Wheelbase	2,280	2,450
Track-front	1,435	1,435
Track-rear	1,445	1,445
Body overhang		
Front	660	660
Rear	505	635
Ground clearance (unladen)	195	195

Items	H65	H76
	WMNUEL1NQ WMRUEL1NQ	WLNUEL1NQ WLRUEL1NQ
Wheel alignment Front wheel alignment Toe-in (at the centre of tyre tread) mm Toe angle (per wheel) Camber Caster Kingpin inclination angle Rear wheel alignment Toe-in (at the centre of tyre tread) mm Camber	 3 ± 2 $0^{\circ}07' \pm 05'$ $0^{\circ}30' \pm 30'$ $3^{\circ}00' \pm 30'$ $11^{\circ}04'$ 0 0°	
Wheels and tyres Tyre size Wheel size Offset mm	 205/65R15 94H 16 x 6JJ 46	

NOTE

(1) *1: indicates vehicles with bumper extension.

(2) *2: indicates vehicles with side moulding.

(3) *3: indicates vehicles with roof rail.

(4) *4: indicates vehicles with roof spoiler.

(VEHICLES FOR BRAZIL)

Items	H76
	WLNUEL1FB, WLRUEL1FB
Dimensions mm Overall length Overall width Overall height (unladen) Wheelbase Track-front Track-rear Body overhang Front Rear Ground clearance (unladen)	 4,030, 4,060*1 1,680, 1,695*2 1,700, 1,740*3, 1,725*4 2,450 1,435 1,445 660 635 195
Wheel alignment Front wheel alignment Toe-in (at the centre of tyre tread) mm Toe angle (per wheel) Camber Caster Kingpin inclination angle Rear wheel alignment Toe-in (at the centre of tyre tread) mm Camber	 3 ± 2 $0^{\circ}07' \pm 05'$ $0^{\circ}30' \pm 30'$ $3^{\circ}00' \pm 30'$ $11^{\circ}04'$ 0 0°

Items	H76
	WLNUEL1FB, WLRUEL1FB
Wheels and tyres	
Tyre size	205/65R15 94H
Wheel size	16 × 6JJ
Offset mm	46

NOTE

(1) *1: indicates vehicles with bumper extension.

(3) *3: indicates vehicles with roof rail.

(2) *2: indicates vehicles with side moulding.

(4) *4: indicates vehicles with roof spoiler.

(VEHICLES FOR HONG KONG)

Items	H66	H76
	WMNUCR1D WMRUCR1D	WLNUCR1D WLRUCR1D
Dimensions mm		
Overall length	3,730, 3,760* ¹	4,030, 4,060* ¹
Overall width	1,680	1,680, 1,695* ²
Overall height (unladen)	1,690, 1,730* ³ , 1,735* ⁴	1,700, 1,740* ³ , 1,725* ⁴
Wheelbase	2,280	2,450
Track-front	1,435	1,435
Track-rear	1,445	1,445
Body overhang		
Front	660	660
Rear	505	635
Ground clearance (unladen)	195	195
Wheel alignment		
Front wheel alignment		
Toe-in (at the centre of tyre tread) mm	3 ± 2	
Toe angle (per wheel)	0°07' ± 05'	
Camber	0°30' ± 30'	
Caster	3°00' ± 30'	
Kingpin inclination angle	11°04'	
Rear wheel alignment		
Toe-in (at the centre of tyre tread) mm	0	
Camber	0°	
Wheels and tyres		
Tyre size	205/65R15 94H	
Wheel size	16 × 6JJ	
Offset mm	46	

NOTE

(1) *1: indicates vehicles with bumper extension.

(3) *3: indicates vehicles with roof rail.

(2) *2: indicates vehicles with side moulding.

(4) *4: indicates vehicles with roof spoiler.

(VEHICLES FOR SOUTH AFRICA)

Items	H65	H76
	WMNUER1S	WLNUE1S, WLRUE1S
Dimensions mm		
Overall length	3,730, 3,760* ¹	4,030, 4,060* ¹
Overall width	1,680	1,680, 1,695* ²
Overall height (unladen)	1,690, 1,730* ³ , 1,735* ⁴	1,700, 1,740* ³ , 1,725* ⁴
Wheelbase	2,280	2,450
Track-front	1,435	1,435
Track-rear	1,445	1,445
Body overhang		
Front	660	660
Rear	505	635
Ground clearance (unladen)	195	195
Wheel alignment		
Front wheel alignment		
Toe-in (at the centre of tyre tread) mm	3 ± 2	
Toe angle (per wheel)	0°07' ± 05'	
Camber	0°30' ± 30'	
Caster	3°00' ± 30'	
Kingpin inclination angle	11°04'	
Rear wheel alignment		
Toe-in (at the centre of tyre tread) mm	0	
Camber	0°	
Wheels and tyres		
Tyre size	205/65R15 94H	
Wheel size	16 × 6JJ	
Offset mm	46	

NOTE(1) *¹: indicates vehicles with bumper extension.(3) *³: indicates vehicles with roof rail.(2) *²: indicates vehicles with side moulding.(4) *⁴: indicates vehicles with roof spoiler.**VEHICLES FOR GCC**

Items	H65	H76
	WMNUELW, WMRUELW	WLNUELW, WLRUELW
Dimensions mm		
Overall length	3,730, 3,760* ¹	4,030, 4,060* ¹
Overall width	1,680	1,680, 1,695* ²
Overall height (unladen)	1,690, 1,730* ³ , 1,735* ⁴	1,700, 1,740* ³ , 1,725* ⁴
Wheelbase	2,280	2,450
Track-front	1,435	1,435
Track-rear	1,445	1,445
Body overhang		
Front	660	660
Rear	505	635
Ground clearance (unladen)	195	195

Items	H65	H76
	WMNUELW, WMRUELW	WLNUELW, WLRUELW
Wheel alignment		
Front wheel alignment		
Toe-in (at the centre of tyre tread) mm	3 ± 2	
Toe angle (per wheel)	0°07' ± 05'	
Camber	0°30' ± 30'	
Caster	3°00' ± 30'	
Kingpin inclination angle	11°04'	
Rear wheel alignment		
Toe-in (at the centre of tyre tread) mm	0	
Camber	0°	
Wheels and tyres		
Tyre size	205/65R15 94H	
Wheel size	16 × 6JJ	
Offset mm	46	

NOTE

(1) *1: indicates vehicles with bumper extension.

(3) *3: indicates vehicles with roof rail.

(2) *2: indicates vehicles with side moulding.

(4) *4: indicates vehicles with roof spoiler.

VEHICLES FOR AUSTRALIA AND NEW ZEALAND

Items	H65	H76
	WMNUER8	WLNUER8, WLRUER8
Dimensions mm		
Overall length	3,730, 3,760* ¹	4,030, 4,060* ¹
Overall width	1,680	1,680, 1,695* ²
Overall height (unladen)	1,690, 1,730* ³ , 1,735* ⁴	1,700, 1,740* ³ , 1,725* ⁴
Wheelbase	2,280	2,450
Track-front	1,435	1,435
Track-rear	1,445	1,445
Body overhang		
Front	660	660
Rear	505	635
Ground clearance (unladen)	195	195
Wheel alignment		
Front wheel alignment		
Toe-in (at the centre of tyre tread) mm	3 ± 2	
Toe angle (per wheel)	0°07' ± 05'	
Camber	0°30' ± 30'	
Caster	3°00' ± 30'	
Kingpin inclination angle	11°04'	
Rear wheel alignment		
Toe-in (at the centre of tyre tread) mm	0	
Camber	0°	
Wheels and tyres		
Tyre size	205/65R15 94H	
Wheel size	16 × 6JJ	
Offset mm	46	

NOTE

(1) *1: indicates vehicles with bumper extension.

(3) *3: indicates vehicles with roof rail.

(2) *2: indicates vehicles with side moulding.

(4) *4: indicates vehicles with roof spoiler.