# CAPACITIES

| Year | Model | Engine Displacement Liters (cc) | Engine ID/VIN | Engine Oil with Filter (qts.) | Transmission (pts.) | | Transfer Case (pts.) | Drive Axle | | Fuel Tank (gal.) | Cooling System (qts.) |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | Manual | Auto. | | Front (pts.) | Rear (pts.) | | |
| 2000 | Expedition | 4.6 (4588) | 6/W | 6.0 | — | ⑨ | 4.0 | 3.7 | 5.5 | ⑥ | 19.4 |
| | Expedition | 5.4 (5409) | L/A | 7.0 | — | ⑨ | 4.0 | 3.7 | 5.5 | ⑥ | 19.4 |
| | F-150 | 4.2 (4195) | 2 | 6.0 | 5.6 | ⑨ | 4.0 | 3.7 | 5.5 | ⑤ | 17.3 |
| | F-150 | 4.6 (4588) | 6/W | 6.0 | 5.6 | ⑨ | 4.0 | 3.7 | 5.5 | ⑤ | 19.4 |
| | F-150 | 5.4 (5409) | L/M/Z/3 | 7.0 | 5.6 | ⑨ | 4.0 | 3.7 | 5.5 | ⑤ | 19.4 |
| | F-250 | 4.6 (4588) | 6/W | 6.0 | 5.6 | ⑨ | 4.0 | 3.7 | 5.5 | ⑤ | 19.4 |
| | F-250 | 5.4 (5409) | L/M/Z | 7.0 | 5.6 | ⑨ | 4.0 | 3.7 | 5.5 | ⑤ | 19.4 |
| | F-Super Duty ① | 5.4 (5409) | L | 7.0 | ② | ⑨ | ⑦ | 6.0 | 6.0 ④ | ⑪ | 19.4 |
| | F-Super Duty ① | 6.8 (6802) | 5 | 7.0 | ② | ⑨ | ⑦ | 6.0 | 6.0 ④ | ⑪ | 19.4 |
| | F-Super Duty ① | 7.3 (7292) | F | 14.0 | ② | ⑨ | ⑦ | 6.0 | 6.0 ④ | ⑪ | 23.0 |
| | Navigator | 5.4 (5409) | L/A | 7.0 | — | ⑨ | 4.0 | 3.7 | 5.5 | 30.0 | 19.4 |

NOTE: All capacities are approximate. Add fluid gradually and check to be sure a proper fluid level is obtained.

① F-Super Duty models 1999-00 include the F-250 Super Duty and above

② Without PTO: 6.0 pts.
With PTO: 12.0 pts.

③ 4X2 with 4R70W: 28.0 pts.
4X4 with 4R70W: 30.0 pts.
4X2 with E4OD: 32.0 pts.
4X4 with E4OD: 33.0 pts.

④ 10.25 inch rear: 7.5 pts.

⑤ 25.0 gallon tank on short bed, 30 gallon tank on long bed

⑥ 4X2 models 26.0 gallon tank, 4X4 models 30 gallon tank

⑦ Without PTO: 4.0 pts.
With PTO: 12.0 pts.

⑧ Manual trans. with standard cooling: 15.0 qts.
Automatic trans. with standard cooling: 16.4 qts.
Manual/automatic trans. with AC: 16.4 qts.
Man/auto trans. with supercooling and AC: 18.0 qts.

⑨ 4X2 with 4R70W: 28.0 pts.
4X4 with 4R70W: 30.0 pts.
4R100 with 20 plate fluid cooler: 34.0 pts.
4R100 with 26 plate fluid cooler: 35.2 pts.

⑩ F250 Heavy Duty 4X2 regular cab midship tank 19.0, aft axle tank 18.2
F250 Heavy Duty 4X2 super cab midship tank 19.0, aft axle tank 18.2
F250 Heavy Duty 4X4 regular cab midship tank 19.0, aft axle tank 18.2
F250 Heavy Duty 4X4 super cab midship tank 19.0, aft axle tank 18.2
F350 chassis cab 4X2 and 4X4 with E4OD trans. midship tank 18.2, aft axle tank 19.0
F350 chassis cab 4X2 and 4X4 without E4OD trans. midship tank 19.0, aft axle tank 19.0
F350 supers cab 4X2 and 4X4 midship tank 19.0, aft axle tank 15.2
F-super duty midship tank 19.0, aft axle tank 19.0
F-super duty motorhome chassis 75.0

⑪ Midship tank 29.0 on F250/350 with standard wheelbase
Midship tank 38.0 on F250/350 with long wheelbase
Aft axle tank 36.0 on standard chassis cab
Optional 19.0 tank in place of 36.0 tank on chassis cab