
CLUTCH

CONTENTS

21109000114

GENERAL INFORMATION	2	CLUTCH PEDAL	4
SERVICE SPECIFICATIONS	2	CLUTCH CONTROL	5
LUBRICANTS	2	Clutch Master Cylinder	6
ON-VEHICLE SERVICE	2		
Clutch Pedal Inspection and Adjustment	2		
Bleeding	3		

GENERAL INFORMATION

21100010093

The clutch is a dry single-disc, diaphragm type; hydraulic pressure is used for the clutch control.

SERVICE SPECIFICATIONS


21100030099

Items	Standard value
Clutch pedal height mm	162–165
Clutch pedal clevis pin play mm	1–3
Clutch pedal free play mm	6–13
Distance between the clutch pedal and the toeboard when the clutch is disengaged mm	85 or more

LUBRICANTS

21100040078


Items	Specified lubricants	Quantity
Clutch fluid	Brake fluid DOT 3 or DOT 4	As required
Push rod assembly	Rubber grease	
Boot		
Release cylinder push rod	MITSUBISHI genuine grease Part No. 0101011	

**ON-VEHICLE SERVICE**


21100090103

CLUTCH PEDAL INSPECTION AND ADJUSTMENT


1. Turn up the carpet, etc. under the clutch pedal.
2. Measure the clutch pedal height.
Standard value (A): 162 – 165 mm




3. If the height of the clutch pedal is outside the standard value, loosen the lock nut and adjust the pedal height to the standard value using the adjusting bolt or push rod.

Clutch pedal clevis pin play

A14W0002

Clutch pedal free play

14W0002

Distance between the clutch pedal and the toeboard when the clutch is disengaged14W0003
00003373

4. Measure the clutch pedal play.

Standard value (B): 1 – 3 mm

5. If the clutch pedal play is not within the standard value, loosen the locking nut and move the push rod to adjust.

Caution

Do not push in the master cylinder push rod at this time.

6. After completing the adjustments, confirm that the clutch pedal free play (measured at the face of the pedal pad) and the distance between the clutch pedal (the face of the pedal pad) and the toeboard when the clutch is disengaged are within the standard value ranges.

Standard value (C): 6–13 mm

Standard value (D): 85 mm or more

7. If the clutch pedal free play and the distance between the clutch pedal and the toeboard when the clutch is disengaged do not agree with the standard values, it is probably the result of either air in the hydraulic system or a faulty master cylinder or clutch. Bleed the air, or disassembly and inspect the master cylinder or clutch.
8. Turn back the carpet, etc.


BLEEDING

21100140099

Specified fluid: Brake fluid DOT 3 or DOT 4

Caution


Use the specified brake fluid. Avoid using a mixture of the specified fluid and other fluid.



A08M0002

CLUTCH PEDAL**REMOVAL AND INSTALLATION****Post-Installation Operation**

Clutch Pedal Adjustment (Refer to P. 21-2.)

**Removal steps**

1. Clutch master cylinder installation nut
2. Master cylinder member bracket installation nut
3. Clevis pin
4. Pedal support member and clutch pedal assembly
5. Bolt
6. Return spring

7. Bushing
8. Pipe
9. Clutch pedal
10. Pedal pad
11. Stopper
12. Adjusting bolt
13. Locking nut
14. Pedal support member

CLUTCH CONTROL

21100190124


REMOVAL AND INSTALLATION**Pre-removal Operation**

- Clutch Fluid Draining
- Air Cleaner Removal


Post-installation Operation

- Air Cleaner Installation
- Clutch Fluid Supplying
- Clutch Line Bleeding (Refer to P.21-3.)
- Clutch Pedal Adjustment (Refer to P. 21-2.)

<L.H. drive vehicles>



<R.H. drive vehicles>

08M0011
00004609**Clutch master cylinder removal steps**

1. Clevis pin
2. Clutch pipe connection
3. Clutch master cylinder

Clutch release cylinder removal steps

4. Clutch pipe connection
5. Clutch release cylinder


Clutch line removal steps

6. Clutch pipe
7. Hose clip
8. Clutch hose

DISASSEMBLY AND REASSEMBLY




21100210103

CLUTCH MASTER CYLINDER



08M0003

00004610




Disassembly steps



1. Piston stopper ring
2. Push rod assembly
3. Boot
4. Piston assembly
5. Reservoir cap
6. Spring pin
7. Reservoir tank
8. Clutch master cylinder body

Caution
Do not disassemble piston assembly.



INSTALLATION SERVICE POINT

◀A▶ PUSH ROD ASSEMBLY INSTALLATION

Set the length of the push rod assembly to the shown dimension to make the adjustment of the clutch pedal easier.