



Specifications

Dimensions

Length		196.7 in (4,995 mm)
Width		71.7 in (1,820 mm)
Height		54.5 in (1,385 mm)
Wheelbase		114.6 in (2,910 mm)
Track	Front	61.0 in (1,550 mm)
	Rear	60.6 in (1,540 mm)

Weights

Gross vehicle weight rating	See the certification label attached to the driver's doorjamb.
-----------------------------	--

Air Conditioning

Refrigerant type	HFC-134a (R-134a)
Charge quantity	24.7 – 26.5 oz (700 – 750 g)
Lubricant type	ND-OIL8

Capacities

Fuel tank		Approx. 18.0 US gal (68 ℓ , 15.0 Imp gal)
Engine coolant	Change* ¹	1.61 US gal (6.1 ℓ , 1.34 Imp gal)
	Total	2.27 US gal (8.6 ℓ , 1.89 Imp gal)
Engine oil	Change* ²	
	Including filter	4.9 US qt (4.6 ℓ , 4.0 Imp qt)
	Without filter	4.5 US qt (4.3 ℓ , 3.8 Imp qt)
	Total	5.6 US qt (5.3 ℓ , 4.7 Imp qt)
Automatic transmission fluid	Change	3.2 US qt (3.0 ℓ , 2.6 Imp qt)
	Total	9.1 US qt (8.6 ℓ , 7.6 Imp qt)
Differential oil	Change	1.11 US qt (1.05 ℓ , 0.92 Imp qt)
	Total	1.16 US qt (1.10 ℓ , 0.97 Imp qt)
Windshield washer reservoir	U.S. Cars	2.6 US qt (2.5 ℓ , 2.2 Imp qt)
	Canada Cars	6.9 US qt (6.5 ℓ , 5.7 Imp qt)

* 1 : Including the coolant in the reserve tank and that remaining in the engine.

Reserve tank capacity:

0.172 US gal (0.65 ℓ , 0.143 Imp gal)

* 2 : Excluding the oil remaining in the engine.

**Lights**

Headlights* ¹	12 V — 55 W (H1) (High beam)
Front turn signal/parking lights	12 V — 27/8 W
Rear turn signal lights	12 V — 21 W
Stop/Taillights	12 V — 21/5 W
Front fog lights	12 V — 55 W (H1)
High-mount brake light	12 V — 21 W
Front side marker lights	12 V — 3 CP
Back-up lights	12 V — 21 W
License plate lights	12 V — 3 CP
Ceiling lights Front	12 V — 5 W
Rear	12 V — 5 W
Trunk light	12 V — 3.4 W
Door courtesy lights	12 V — 3.4 W
Vanity mirror light	12 V — 2 W

* 1 : Low beam headlight bulbs are a type of high voltage discharge tube (D2R).

Battery

Capacity	12 V — 55 AH/5 HR 12 V — 65 AH/20 HR
----------	---

Fuses

Interior	See page 305 or the fuse label attached to the inside of the fuse box door under the dashboard.
Under-hood	See page 304 or the fuse box cover.

Engine

Type	Water cooled 4-stroke SOHC V-6 gasoline engine
Bore x Stroke	3.54 x 3.58 in (90 x 91 mm)
Displacement	212 cu-in (3,474 cm ³)
Compression ratio	9.6 : 1
Spark plugs	See spark plug maintenance section page 246 .

Alignment

Toe	Front	0.00 in (0.0 mm)
	Rear	in 0.08 in (2.0 mm)
Camber	Front	0°
	Rear	— 0° 30'
Caster	Front	2° 50'

Tires

Size	Front/Rear	P225/55R16 94V
	Spare	T135/80D16 101M
Pressure	Front/Rear	30 psi (210 kPa , 2.1 kgf/cm ²)
	Spare	60 psi (420 kPa , 4.2 kgf/cm ²)