
GROUP 0**GENERAL****CONTENTS**

VEHICLE IDENTIFICATION	0-2	MAJOR SPECIFICATIONS	0-2
------------------------------	-----	----------------------------	-----

VEHICLE IDENTIFICATION

M4000001000695

MODELS

Model code		Engine model	Price class	Transmission model	Fuel supply system
CU2W	XNMML6	4G63-DOHC-Non-Turbo (1,997 mL)	Invite	F5M42 <2WD, 5M/T>	MPI
	XNMMZL6			W5M42 <4WD, 5M/T>	
	XNHMZL6		Intense		
	XNXFZL6	4G63-DOHC-Turbo (1,997 mL)	Turbo	W5M51 <4WD, 5M/T>	
CU5W	XNMYZL6	4G69-SOHC MIVEC (2,378 mL)	Invite	W5M42 <4WD, 5M/T>	
	XRMYZL6			W4A42 <4WD, 4A/T with sport mode>	
	XRMYZR6				
	XNHYZL6		Intense	W5M42 <4WD, 5M/T>	
	XRHYZL6			W4A4B <4WD, 4A/T with sport mode>	
	XRHYZR6				

MAJOR SPECIFICATIONS

M4000003000550

Items			CU2W			
			XNMML6	XNMMZL6	XNHMZL6	XNXFZL6
Vehicle dimension mm	Overall length		4,545			
	Overall width		1,750		1,780	
	Overall height (unladen)		1,620/1,670 ^{*1}			
	Wheelbase		2,625			
	Track	Front	1,495			
		Rear	1,505			
	Front overhang		945			
	Rear overhang		975			
Ground clearance (unladen)		195				

Items			CU2W			
			XNMML6	XNMMZL6	XNHMZL6	XNXFZL6
Vehicle wheel alignment	Front	Toe-in (at the centre of tyre tread) mm	1 ± 2			
		Toe angle (per wheel)	0°03' ± 05'			
		Toe-out angle on turns (inner wheel outer wheel at 20°)	22°00' ±1° 30'			
		Camber	-0°10' ± 30' ^{*2}			
		Caster	3°15' ± 30' ^{*2}			
		Kingpin inclination angle	12°25' ± 1°30'			
		Side slip (per 1m) mm	0 ± 3			
	Steering angle	Inner wheels	34°50' ± 1°30'			
		Outer wheels (reference)	29°20'			
	Rear	Toe-in (at the centre of tyre tread) mm	3 ± 2			
		Toe angle (per wheel)	0°08' ± 05'			
		Camber	-0°40' ± 30' ^{*2}			
Wheels and tyres		Tyre size	215/60 R16 95H			215/55 R17 94V
		Wheel size	16 × 6JJ			17 × 6.5JJ
		Offset mm	46			38

NOTE:

^{*1}: Vehicles with roof rails.

^{*2}: Difference between right and left wheels must be less than 30'.

Items			CU5W			
			XNMYZL6	XRMYZL6/R6	XNHYZL6	XRHYZL6/R6
Vehicle dimension mm	Overall length		4,545			
	Overall width		1,750		1,780	
	Overall height (unladen)		1,620/1,670 ^{*1}			
	Wheelbase		2,625			
	Track	Front	1,495			
		Rear	1,505			
	Front overhang		945			
	Rear overhang		975			
Ground clearance (unladen)		195				

Items			CU5W			
			XNMYZL6	XRMYZL6/R6	XNHYZL6	XRHYZL6/R6
Vehicle wheel alignment	Front	Toe-in (at the centre of tyre tread) mm	1 ± 2			
		Toe angle (per wheel)	0°03' ± 05'			
		Toe-out angle on turns (inner wheel outer wheel at 20°)	22°00' ±1° 30'			
		Camber	-0°10' ± 30' ^{*2}			
		Caster	3°15' ± 30' ^{*2}			
		Kingpin inclination angle	12°25' ± 1°30'			
		Side slip (per 1m) mm	0 ± 3			
	Steering angle	Inner wheels	34°50' ± 1°30'			
		Outer wheels (reference)	29°20'			
	Rear	Toe-in (at the centre of tyre tread) mm	3 ± 2			
		Toe angle (per wheel)	0°08' ± 05'			
		Camber	-0°40' ± 30' ^{*2}			
Wheels and tyres		Tyre size	215/60 R16 95H			
		Wheel size	16 × 6JJ			
		Offset mm	46			

NOTE:

1: Vehicles with roof rails.*2: Difference between right and left wheels must be less than 30'.*