

Automatic Transmission — Section 14

		MEASUREMENT	STANDARD (NEW)	SERVICE LIMIT
Transmission fluid	Capacity ℓ (US qt, Imp qt)		7.0 (7.4, 6.2) for overhaul 2.9 (3.1, 2.6) for fluid change	
Hydraulic pressure kPa (kgf/cm ² , psi)	Line pressure at 2,000 rpm in D or 1 position		830 – 880 (8.5 – 9.0, 121 – 128)	785 (8.0, 114)
	1st clutch pressure at 2,000 rpm in D or 1 position		490 (5.0, 71) Fully closed throttle 880 (9.0, 128) throttle more than 3/16 opened	440 (4.5, 64) Fully closed throttle 785 (8.0, 114) throttle more than 3/16 opened
	2nd clutch pressure at 2,000 rpm in D position			
	3rd clutch pressure at 2,000 rpm in D position			
	4th clutch pressure at 2,000 rpm in D position			
	1st-hold clutch pressure at 2,000 rpm in 1 position		830 – 880 (8.5 – 9.0, 121 – 128)	785 (8.0, 114)
	2nd clutch pressure at 2,000 rpm in 2 position			
	4th clutch pressure at 2,000 rpm in R position			
	Throttle B pressure Throttle fully closed 			


* Clutch end plate diameter: 1st: 116 mm (4.57 in)
1st-hold, 2nd, 3rd and 4th: 120 mm (4.72 in)

(cont'd)

Unit of length: mm (in)

Automatic Transmission — Section 14

	MEASUREMENT	STANDARD (NEW)	SERVICE LIMIT
Transmission (cont'd)	Selector hub O.D.	55.67 – 55.70 (2.192 – 2.193)	Wear or damage
	Thrust washer thickness		
	Mainshaft 4th gear right side	4.45 – 4.55 (0.175 – 0.179)	Wear or damage
	Mainshaft 4th gear left side	3.45 – 3.55 (0.136 – 0.140)	Wear or damage
	Mainshaft 1st gear right side	1.45 – 1.50 (0.057 – 0.059)	1.40 (0.055)
	Mainshaft 1st gear left side	2.43 – 2.50 (0.096 – 0.098)	Wear or damage
	Countershaft 3rd gear collar length	1 35.425 – 35.440 (1.3947 – 1.3953)	_____
		2 35.440 – 35.455 (1.3953 – 1.3959)	_____
		3 35.455 – 35.470 (1.3959 – 1.3965)	_____
		4 35.470 – 35.485 (1.3965 – 1.3970)	_____
		5 35.485 – 35.500 (1.3970 – 1.3976)	_____
		6 35.500 – 35.515 (1.3976 – 1.3982)	_____
	Countershaft 2nd gear spacer length	17.90 – 17.95 (0.705 – 0.707)	_____
	Cotter thickness	1 1.975 – 2.000 (0.078 – 0.079)	_____
		2 2.000 – 2.025 (0.079 – 0.080)	_____
		3 2.025 – 2.050 (0.080 – 0.081)	_____
		4 2.050 – 2.075 (0.081 – 0.082)	_____
		5 2.075 – 2.100 (0.082 – 0.083)	_____
		6 2.100 – 2.125 (0.083 – 0.084)	_____
		7 2.125 – 2.150 (0.084 – 0.085)	_____
		8 2.150 – 2.175 (0.085 – 0.086)	_____
		9 2.175 – 2.200 (0.086 – 0.087)	_____
		10 2.200 – 2.225 (0.087 – 0.088)	_____
		11 2.225 – 2.250 (0.088 – 0.089)	_____
		12 2.250 – 2.275 (0.089 – 0.090)	_____
		13 2.275 – 2.300 (0.090 – 0.091)	_____
		14 2.300 – 2.325 (0.091 – 0.092)	_____
		15 2.325 – 2.350 (0.092 – 0.093)	_____
		16 2.350 – 2.375 (0.093 – 0.094)	_____
	Cotter retainer thickness	1 2.97 – 3.00 (0.117 – 0.118)	_____
		2 3.00 – 3.03 (0.118 – 0.119)	_____
		3 3.03 – 3.06 (0.119 – 0.120)	_____
		4 3.06 – 3.09 (0.120 – 0.122)	_____
		5 3.09 – 3.12 (0.122 – 0.123)	_____
	Countershaft reverse gear thrust washer thickness	1.45 – 1.50 (0.057 – 0.059)	1.40 (0.055)
	Countershaft 1st gear collar length	1 62.50 – 62.55 (2.461 – 2.463)	_____
		2 62.60 – 62.65 (2.465 – 2.467)	_____
	Thrust washer thickness		
	Countershaft 1st gear left side	3.43 – 3.50 (0.135 – 0.138)	Wear or damage
	Secondary shaft 2nd gear	4.45 – 4.55 (0.175 – 0.179)	Wear or damage
	Secondary shaft spacer 31 mm length	33.00 – 33.05 (1.299 – 1.301)	_____
	End play		
	Mainshaft 4th gear	0.10 – 0.22 (0.004 – 0.009)	_____
	Mainshaft 1st gear	0.08 – 0.33 (0.003 – 0.013)	_____
	Countershaft 3rd gear	0 – 0.03 (0 – 0.001)	} Adjust with a 3rd gear collar or cotters
	Countershaft 2nd gear	0 – 0.05 (0 – 0.002)	
	Countershaft 4th gear	0.05 – 0.11 (0.002 – 0.004)	Adjust with a cotter retainer
	Countershaft reverse gear	0.10 – 0.25 (0.004 – 0.010)	_____
	Countershaft 1st gear	0.20 – 0.31 (0.008 – 0.012)	Adjust with a 1st gear collar
	Secondary shaft 2nd gear	0.01 – 0.11 (0.0004 – 0.0043)	Adjust with a thrust washer
	Reverse idler gear	0.05 – 0.18 (0.002 – 0.007)	_____
	Secondary shaft 2nd gear thrust washer depth "d"	0 (0)	_____
		0 – 0.03 (0 – 0.001)	_____
		0.03 – 0.06 (0.001 – 0.002)	_____
		0.06 – 0.09 (0.002 – 0.004)	_____
		0.09 – 0.12 (0.004 – 0.005)	_____



(cont'd)

Standards and Service Limits

Automatic Transmission (cont'd) — Section 14

	MEASUREMENT	STANDARD (NEW)			
		Wire Dia.	O.D.	Free Length	No. of Coils
Spring	Idle shaft spring A	0.7 (0.028)	5.7 (0.224)	14.6 (0.575)	7.0
	Servo detent spring	1.0 (0.039)	7.6 (0.299)	14.8 (0.583)	5.5
	Regulator valve spring A	1.58 x 2.0 (0.062 x 0.079)	14.7 (0.579)	88.6 (3.488)	20.9
	Regulator valve spring B	1.8 (0.071)	9.6 (0.378)	44.0 (1.732)	14.7
	Stator reaction spring	6.0 (0.236)	38.4 (1.512)	30.3 (1.193)	2.0
	Torque converter check valve spring	1.1 (0.043)	8.4 (0.331)	41.8 (1.646)	15.7
	Relief valve spring	1.1 (0.043)	8.4 (0.331)	44.4 (1.748)	19.5
	Cooler relief valve spring	1.2 (0.047)	8.4 (0.331)	35.7 (1.406)	16.5
	One-way relief valve spring	0.9 (0.035)	6.4 (0.252)	25.1 (0.988)	11.9
	LSD relief valve spring	0.8 (0.031)	8.4 (0.331)	37.3 (1.469)	12.1
	2nd orifice control valve spring	0.8 (0.031)	8.1 (0.319)	47.9 (1.886)	16.0
	3rd orifice control valve spring	0.9 (0.035)	8.6 (0.339)	48.3 (1.902)	16.6
	4th exhaust valve spring	0.6 (0.024)	7.6 (0.299)	24.4 (0.961)	7.9
	Throttle valve B spring A/B/C/D	0.9 (0.035)	7.1 (0.280)	29.0 (1.142)	12.6
	1-2 shift valve spring	0.9 (0.035)	8.6 (0.339)	40.4 (1.591)	14.5
	2-3 shift valve spring	0.8 (0.031)	7.0 (0.276)	43.7 (1.720)	21.2
	3-4 shift valve spring	0.8 (0.031)	7.0 (0.276)	43.7 (1.720)	21.2
	1st-hold accumulator spring	3.4 (0.134)	24.3 (0.957)	64.7 (2.547)	6.7
	1st accumulator spring	2.3 (0.091)	20.0 (0.787)	104.6 (4.118)	14.8
	4th accumulator spring	3.0 (0.118)	18.0 (0.709)	84.5 (3.327)	12.8
	2nd accumulator spring	3.3 (0.130)	20.2 (0.795)	78.0 (3.071)	11.8
	3rd accumulator spring	3.2 (0.126)	19.0 (0.748)	88.6 (3.488)	14.3
	Lock-up shift valve spring	1.0 (0.039)	8.6 (0.339)	51.3 (2.020)	19.8
	Lock-up timing valve B spring	0.8 (0.031)	5.6 (0.220)	27.8 (1.094)	16.4
	Lock-up control valve spring A/B/C	0.8 (0.031)	6.6 (0.260)	38.3 (1.508)	25.0
	Servo control valve spring	1.0 (0.039)	8.1 (0.319)	53.5 (2.106)	20.8
	Modulator valve spring A/B	1.4 (0.055)	9.4 (0.370)	33.0 (1.299)	10.5
	CPC valve spring A/B/C	1.0 (0.039)	6.8 (0.268)	32.1 (1.264)	15.6
	4-3 kick down valve spring	0.9 (0.035)	6.6 (0.260)	30.7 (1.209)	12.9
	3-2 kick down valve spring	1.0 (0.039)	6.1 (0.240)	27.1 (1.067)	13.4
	2nd exhaust valve spring	1.0 (0.039)	6.1 (0.240)	27.1 (1.067)	13.4