

Standards and Service Limits

Manual Transmission — Section 13

	MEASUREMENT	STANDARD (NEW)	SERVICE LIMIT
Transmission oil	Capacity ℓ (US qt, Imp qt)	2.8 (3.0, 2.5) for overhaul 2.7 (2.9, 2.4) for oil change	
Mainshaft	Diameter of ball bearing contact area (transmission housing side) Diameter of needle bearing contact area Diameter of ball bearing contact area (clutch housing side) Runout End play	30.984-31.000 (1.220-1.221) 42.984-43.000 (1.692-1.693) 32.002-32.018 (1.260-1.261) 0.02 (0.001) max. 0.14-0.21 (0.006-0.008)	30.93 (1.2177) 42.93 (1.690) 31.95 (1.258) 0.05 (0.002) Adjust with a shim.
Mainshaft 3rd gear	I.D. End play Thickness	49.009-49.025 (1.9295-1.9301) 0.06-0.21 (0.002-0.008) 35.92-35.97 (1.414-1.416)	49.08 (1.9323) 0.3 (0.012) 35.80 (1.409)
Mainshaft 4th gear	I.D. End play Thickness	49.009-49.025 (1.9295-1.9301) 0.06-0.21 (0.002-0.008) 35.92-35.97 (1.414-1.416)	49.08 (1.9323) 0.3 (0.012) 35.80 (1.409)
Mainshaft 5th gear	I.D. End play Thickness	47.009-47.025 (1.8507-1.8514) 0.06-0.21 (0.002-0.008) 34.92-34.97 (1.375-1.377)	47.08 (1.8535) 0.3 (0.012) 34.80 (1.370)
Spacer collar (Mainshaft)	I.D. O.D. Length 4th gear side 5th gear side 4th gear side 5th gear side	36.002-36.012 (1.417-1.418) 42.989-43.000 (1.692-1.693) 41.989-42.000 (1.653-1.654) 29.53-29.58 (1.163-1.165) 28.53-28.58 (1.123-1.125)	36.06 (1.420) 42.94 (1.691) 41.94 (1.651) 29.51 (1.162) 28.51 (1.122)

cardiagn.com

Manual Transmission — Section 13

	MEASUREMENT	STANDARD (NEW)	SERVICE LIMIT
Countershaft	Diameter of needle bearing contact area (clutch housing side) Diameter of needle and ball bearing contact area (transmission housing side) Runout	43.974 – 43.990 (1.731 – 1.732) 33.984 – 34.000 (1.338 – 1.339) 0.02 (0.001) max.	43.92 (1.729) 33.93 (1.336) 0.05 (0.002)
Countershaft 1st gear	I.D. End play (when tightened by the specified torque)	60.510 – 60.529 (2.382 – 2.383) 0.04 – 0.10 (0.002 – 0.004)	60.58 (2.385) Adjust with a washer.
Countershaft 2nd gear	I.D. End play (when tightened by the specified torque)	57.010 – 57.029 (2.244 – 2.245) 0.04 – 0.10 (0.002 – 0.004)	57.08 (2.247) Adjust with a collar.
Countershaft reverse gear	Diameter of needle bearing contact area	54.487 – 54.500 (2.145 – 2.146)	54.43 (2.143)
Spacer collar (Countershaft)	I.D. O.D.	43.046 – 43.056 (1.6947 – 1.6951) 51.987 – 52.000 (2.0467 – 2.0472)	43.10 (1.697) 51.94 (2.045)
Reverse idler gear shaft	O.D.	21.987 – 22.000 (0.8656 – 0.8661)	21.93 (0.8634)
Reverse driven gear and reverse drive gear	I.D.	28.007 – 28.020 (1.1026 – 1.1031)	28.07 (1.1051)
Oil pump	Driven gear boss-to-transmission housing clearance Driven gear thickness Inner-to-outer rotor radial clearance Pump body-to-outer rotor radial clearance Pump body-to-outer rotor side clearance	0.3 – 0.8 (0.01 – 0.03) 17.0 – 17.1 (0.669 – 0.673) 0.14 (0.006) max. 0.1 – 0.2 (0.004 – 0.008) 0.03 – 0.10 (0.001 – 0.004)	0.9 (0.04) 16.9 (0.665) 0.20 (0.008) 0.22 (0.009) 0.15 (0.006)
Synchro ring	Ring-to-gear clearance (ring pushed against gear)	0.85 – 1.10 (0.033 – 0.043)	0.4 (0.016)
Dual cone synchro ring	Clearance (ring pushed against gear) Outer synchro ring-to-gear Synchro cone-to-gear Outer synchro ring-to-synchro cone	0.95 – 1.68 (0.037 – 0.066) 0.5 – 1.0 (0.020 – 0.039) 0.5 – 1.0 (0.020 – 0.039)	0.6 (0.024) 0.3 (0.012) 0.3 (0.012)
Shift fork	Finger thickness 1st/2nd shift fork 3rd/4th shift fork 5th shift fork Reverse shift fork Finger-to-synchro sleeve clearance	8.9 – 9.0 (0.350 – 0.354) 7.4 – 7.5 (0.291 – 0.295) 6.4 – 6.5 (0.252 – 0.256) 6.4 – 6.5 (0.252 – 0.256) 0.45 – 0.65 (0.018 – 0.026)	— — — — 1.0 (0.039)
Reverse shift arm	Arm-to-5th/reverse shift piece clearance Groove width Arm-to-reverse shift fork clearance Diameter (at the contact point with the reverse shift fork)	0.05 – 0.30 (0.002 – 0.012) 7.05 – 7.20 (0.278 – 0.283) 0.05 – 0.35 (0.002 – 0.014) 12.8 – 13.0 (0.504 – 0.512)	0.5 (0.02) — 0.5 (0.02) —
Shift arm	Arm-to-shift piece clearance Diameter (at the contact point with the shift piece)	0.05 – 0.25 (0.002 – 0.010) 12.9 – 13.0 (0.508 – 0.512)	0.5 (0.02) —
Interlock	Interlock-to-select arm clearance Diameter (at the contact point with the select arm)	0.03 – 0.15 (0.001 – 0.006) 11.95 – 12.00 (0.470 – 0.472)	— —
Shift piece	Shift piece-to-shift forks and 5th/reverse shift piece clearance Diameter (at the contact point with the shift forks and 5th/reverse shift piece)	0.2 – 0.5 (0.008 – 0.020) 11.9 – 12.0 (0.469 – 0.472)	0.6 (0.024) —