

Unit of length: mm (in)

Fuel and Emission — Section 11

	MEASUREMENT	STANDARD (NEW)
Pressure regulator	Pressure kPa (kg/cm ² , psi)	330-370 (3.30-3.70, 47-53)
Fuel tank	Capacity ℓ (US gal, Imp gal)	70 (18.5, 15.4)
Engine	Fast idle rpm	1,100-1,900
	Idle speed rpm (with headlight and cooling fan off)	800 ± 50 (M/T: neutral) 780 ± 50 (A/T: N or P position)
	Idle CO % max.	0.1

Clutch — Section 12

	MEASUREMENT	STANDARD (NEW)	SERVICE LIMIT
Clutch pedal	Pedal height to floor	176.2 (6.94)	
	Stroke	125 (4.92)	
	Pedal play	9-15 (0.35-0.59)	
	Disengagement height to floor	92 (3.62) min.	
Pressure plate	Warpage	0.03 (0.001) max.	0.15 (0.006)
1st clutch disc	Thickness	8.3-9.0 (0.33-0.35)	5.9 (0.23)
	Rivet head depth	1.1 (0.04) min.	0.2 (0.01)
2nd clutch disc	Thickness	7.6-8.3 (0.30-0.33)	5.4 (0.21)
	Rivet head depth	1.1 (0.04) min.	0.2 (0.01)
Mid plate	Warpage	0.05 (0.002) max.	0.15 (0.006)
Flywheel	Clutch surface runout	0.05 (0.002) max.	0.15 (0.006)