

Service Manual: MAINTENANCE AND LUBRICATION

SPECIFICATIONS > APPROXIMATE FLUID CAPACITIES

Maintenance Procedure	Link
Hydraulic Brake System Capacities	Approximate Fluid Capacities
Rear Drive Axle Capacities	Approximate Fluid Capacities
Engine Heating and Cooling Capacities	Approximate Fluid Capacities
HVAC Capacities	Approximate Fluid Capacities
Maintenance and Lubrication	Approximate Fluid Capacities
Engine Controls and Fuel Capacities - 2.0L (LTG)	Approximate Fluid Capacities
Engine Controls and Fuel Capacities - 3.6L (LGX)	Approximate Fluid Capacities
Engine Controls and Fuel Capacities - 6.2L (LT1)	Approximate Fluid Capacities
Engine Mechanical - 2.0L (LTG)	Approximate Fluid Capacities
Engine Mechanical - 3.6L (LGX)	Approximate Fluid Capacities
Engine Mechanical - 6.2L (LT1)	Approximate Fluid Capacities
Automatic Transmission Fluid Capacities - 8L45 (M5T) or 8L90 (M5U)	Approximate Fluid Capacities
Manual Transmission Fluid Capacities - Tremec 6-Speed (MM6 M13)	Approximate Fluid Capacities (MM6) Approximate Fluid Capacities (M13)

SPECIFICATIONS > FLUID AND LUBRICANT RECOMMENDATIONS

Usage	Fluid/Lubricant
Propeller Shaft Splines	Lubricant 19257121 (Canadian P/N 19257122) or equivalent meeting GM Specification 9985830
Engine Oil	Engine oil meeting the dexos1™ specification of the proper SAE viscosity grade. AC Delco dexos1 Synthetic Blend is recommended.
Engine Coolant	50/50 mixture of clean, drinkable water and use only DEX-COOL Coolant.
Hydraulic Brake System	DOT 3 Hydraulic Brake Fluid GM P/N 88862806 (Canadian P/N 88862807)
Hydraulic Clutch System	DOT 3 Hydraulic Brake Fluid GM P/N 88862806 (Canadian P/N 88862807)
Windshield Washer	Automotive windshield washer fluid that meets regional freeze protection requirements

Parking Brake Cable Guides	Chassis Lubricant GM P/N 12377985 (Canadian P/N 88901242) or lubricant meeting requirements of NLGI #2, Category LB or GC-LB
Automatic Transmission	DEXRON®-HP Automatic Transmission Fluid (GM Part No. 19300536, in Canada 19300537)
Manual Transmission - V6 Engine	DEXRON®-VI Manual Transmission Fluid GM P/N 88861037 (Canadian P/N 19264717)
Manual Transmission - V8 Engine	Manual Transmission Fluid GM P/N 88861800 (Canadian P/N 88861801)
Rear Axle (V6 Engine with Automatic Transmission)	Dexron non-LSD Gear Oil GM P/N 88863089 (Canadian P/N 88863090)
Rear Axle (V6 Engine with Manual Transmission)	Dexron LS Gear Oil 75W90 Limited Slip GM P/N 88862624 (Canadian P/N 88862625)
Rear Axle (V8 Engine)	Dexron LS Gear Oil 75W90 Limited Slip GM P/N 88862624 (Canadian P/N 88862625)
Key Lock Cylinders	Multi-Purpose Lubricant, Superlube GM P/N 12346241 (Canadian P/N 10953474)
Hood Latch Assembly, Secondary Latch, Pivots, Spring Anchor, and Release Pawl	Lubriplate Lubricant Aerosol GM P/N 89021668 (Canadian P/N 89021674) or lubricant meeting requirements of NLGI #2, Category LB or GC-LB
Hood, Door, and Folding Seat Hinges	Multi-Purpose Lubricant, Superlube GM P/N 12346241 (Canadian P/N 10953474)
Weatherstrip Conditioning	Weatherstrip Lubricant GM P/N 3634770 (Canadian P/N 10953518) or Dielectric Silicone Grease GM P/N 12345579 (Canadian P/N 10953481)

SPECIFICATIONS > MAINTENANCE ITEMS

Maintenance Procedure	Link
Approximate Fluid Capacities	Approximate Fluid Capacities
Fluid and Lubricant Recommendations	Fluid and Lubricant Recommendations
Maintenance Replacement Parts	Maintenance Replacement Parts
GM Oil Life System Resetting	GM Oil Life System Resetting
Tire Pressure Indicator Sensor Learn	Tire Pressure Indicator Sensor Learn
Passenger Compartment Air Filter Replacement	Passenger Compartment Air Filter Replacement
Brake Pad Inspection	Brake Pad Inspection
Cooling System Draining and Filling	Cooling System Draining and Filling (GE 47716) Cooling System Draining and Filling (Static Fill)

Hydraulic Brake System Bleeding	Hydraulic Brake System Bleeding (Manual J55, J6G) Hydraulic Brake System Bleeding (Pressure J55, J6G) Hydraulic Brake System Bleeding (Manual JL9) Hydraulic Brake System Bleeding (Pressure JL9)
Hydraulic Clutch System Bleeding	Hydraulic Clutch System Bleeding
Air Cleaner Element Replacement - 2.0L (LTG)	Air Cleaner Element Replacement
Air Cleaner Element Replacement - 3.6L (LGX)	Air Cleaner Element Replacement
Air Cleaner Element Replacement - 6.2L (LT1)	Air Cleaner Element Replacement
Spark Plug Replacement - 2.0L (LTG)	Spark Plug Replacement
Spark Plug Replacement - 3.6L (LGX)	Spark Plug Replacement
Spark Plug Replacement - 6.2L (LT1)	Spark Plug Replacement
Drive Belt Replacement - 2.0L (LTG)	Drive Belt Replacement
Drive Belt Replacement - 3.6L (LGX)	Drive Belt Replacement
Drive Belt Replacement - 6.2L (LT1)	Drive Belt Replacement - Accessory
Manual Transmission Fluid Drain and Fill -Tremec 6-Speed (MM6 M13)	Transmission Fluid Drain and Fill (M13 Without Y4Q) Transmission Fluid Drain and Fill (MM6)

SPECIFICATIONS > MAINTENANCE REPLACEMENT PARTS

Replacement parts identified below by name, part number, or specification can be obtained from your dealer.

Part	GM Part Number	ACDelco Part Number
Engine Air Cleaner 3.6L V6 Engine	20857930	A3137C
Engine Air Cleaner 6.2L V8 Engine	92276982	-
Engine Oil Filter		
• 3.6L V6 Engine	19330000	PF63E
• 6.2L V8 Engine	12640445	PF64
Passenger Compartment Air Filter	13508023	CF185
Spark Plugs		
• 3.6L V6 Engine	12646780	41-130

• 6.2L V8 Engine	12622441	41-114
Wiper Blades		
• •Driver Side - 55.8 cm (22 in)	23360288	-
• •Passenger Side - 50.8 cm (20 in)	23360287	-

MAINTENANCE > MAINTENANCE SCHEDULE (NORTH AMERICAN EMISSIONS)

The Maintenance Schedule information will only be found in the Owner's Manual.

Refer to the Maintenance Schedule subsection of the Owner's Manual, or you may be able to use the Search information function using the words Scheduled Maintenance.

MAINTENANCE > GM OIL LIFE SYSTEM RESETTNG

When the system has calculated that oil life has been diminished, it will indicate that an oil change is necessary. A CHANGE ENGINE OIL message or light will come on. Change the engine oil as soon as possible within the next 600 miles (1000 km). It is possible that, if driving under the best conditions, the oil life system may not indicate that an oil change is necessary for over a year. However, the engine oil and filter must be changed at least once a year and at this time the system must be reset.

If the system is ever reset accidentally, change the engine oil at 3, 000 miles (5000 km) since last oil change.

MAINTENANCE > GM OIL LIFE SYSTEM RESETTNG > HOW TO RESET THE ENGINE OIL LIFE SYSTEM

Vehicles with Driver Information Center (DIC)

1. Press the option button on the DIC until ENGINE OIL MONITOR appears on the DIC screen.
2. Press the set/reset button to reset the system. The next screen indicates that the CHANGE OIL SOON message has been reset. If the vehicle has the uplevel DIC, when the gauges button is pressed and the OIL LIFE REMAINING mode appears, it should read 100 percent OIL LIFE REMAINING.
3. Turn the key to OFF.

Vehicles without DIC

1. With the engine OFF, turn the ignition key to RUN.
2. Fully press and release the accelerator pedal slowly three times within five seconds.

3. Turn the key to OFF, than start the vehicle.

If the light or message comes back on when you start the vehicle, the OIL LIFE SYSTEM has not reset.
Repeat the procedure.

cardiagn.com